



**RCA**  
Communications Systems

**prodigi™** SERIES  
PROFESSIONAL DIGITAL RADIO PRODUCTS



**RDR4220** UHF / VHF

**RDR4250** UHF / VHF

**RDR4280** UHF / VHF

The Intelligent Choice for  
Digital Two-Way Radio Communication



**VERSATILE & AFFORDABLE!**

**prodigi**<sup>™</sup>  
PROFESSIONAL DIGITAL RADIO PRODUCTS

The RCA PRODIGI<sup>™</sup> Radio Series is compatible with other DMR Digital radios on the market. Operational in both digital and analog modes, the PRODIGI<sup>™</sup> Radio Series delivers crystal clear, dependable communication. RDR4220, RDR4250 and RDR4280 are designed to be used in a wide range of applications. Industries such as oil and gas, manufacturing, construction, facility management, security, hotels and resorts, casinos and more, can benefit from its basic push to talk functionality and advanced security and emergency features.

## RDR4220 / RDR4250 / RDR4280 FEATURES

**ADVANCED MULTI-MODE FUNCTIONALITY** With different operating modes — Conventional Analog, Conventional Digital DMR Tier II, Digital DMR based PRODIGI<sup>™</sup> Plus, the portable will truly meet even the most demanding communication needs. The RCA RDR42x0 series digital portables radios are designed to connect your workforce efficiently and provide you with reliable communication allowing you focus on growing your business.

**CROSS-BRAND COMPATIBILITY** Utilizing the DMR Digital technology according to the ETSI TS 102 361-1,-2,-3 Standards the RDR42x0 series portables are compatible with all RCA two-way radios as well as all other major brands, including digital equipment, such as Motorola, Hytera and Vertex series digital two-way radios and repeaters.

**INDUSTRIAL DURABILITY AND RELIABILITY** Designed with durability in mind with lightweight and rugged aluminum alloy die-cast chassis, 3.5 mm thick high quality, polycarbonate thermoplastic housing with superior toughness, flame retardancy, scratch and heat resistance and 7x battery locking points to the radio chassis.

**WATERPROOF AND DUSTPROOF DESIGN** The RDR42x0 series portables are designed and built with the most demanding conditions in mind. Your team needs radios that will not fail them, regardless of the working environment. The radios are designed to the Military 810C, D, E, F, G and the IP67 Waterproof and Dustproof standards.

**FEATURE RICH AND VERSATILE** The RDR42x0 series portables come in 3 different models, the standard non-display RDR4220 unit; the upgraded RDR4250 with large, 1.8 inch Full Color Display and navigation keys; the advanced RDR4280 unit with a large, 1.8 inch Full Color Display, full keypad. Businesses, Departments and Government Agencies can choose the best model for their needs, taking advantage of advanced features such as Caller ID, Group and Private Call, Radio Check, Radio Monitor, Radio Enable/Disable, Emergency, Man Down, Lone Worker Alerts, Text Messaging, Pre-saved Status Messaging, Encryption and more.

**IMPROVED COMMUNICATION RANGE** The RDR42x0 Radios utilize the DMR digital technology allowing for the transmissions to stay clear from background noise regardless of the distance between two radio units, providing virtually no deterioration of the voice quality, thus increasing the usable coverage area where analog communication will be very poor or not possible at all.

**FULL SHIFT PERFORMANCE** The RCA PRODIGI<sup>™</sup> RDR42x0 series portables provide up to 40% improved battery performance in digital mode over analog, allowing for longer operating time on a single battery charge. With a typical duty cycle of 5 (Rx) - 5 (Tx) - 90 (Stand By), the RDR4380 color display unit with 2300mAh Lithium Ion battery can provide up to 10 hours of operation in Analog mode and up to 14 hours of operation in Digital mode.

**INTRINSICALLY SAFE OPTION** Certified to the requirements of UL 913 5th Ed., TIA 4950-A, CSA C22.2 No. 157- 92 | Class I, II, III; Division 1; Groups C-G; Division 2; Groups A-G; Temp T3C (with B4223LIIS IS Approved Battery Only) for use in hazardous locations where flammable gas, vapors or combustible dust may be present. The RDR42x0 Series Intrinsically Safe Certified Radios can be used in a wide range of applications and industries such as Oil and Gas Extraction, Chemical and Paint Manufacturing, Refineries and more.

**AVAILABLE ADVANCED OPTIONS** When workers safety and communication security are of utmost importance, the RDR42x0 radios offer optional GPS Location tracking service\* and advanced 40-bit ARC4 type encryption. Encrypting your radio communications and tracking your asset's location results in improved worker safety, increased productivity and shortened incident response time.

**INDUSTRY LEADING WARRANTY** The RCA RDR42x0 series portables are backed standard by an industry leading, hassle-free Three (3) Year Warranty.



RDR4220

RDR4250

RDR4280

\*Requires compatible dispatch console. Requires outdoor use to access satellite signals. Digital mode only.



\*Intrinsically Safe Models Available

# RDR4220 / RDR4250 / RDR4280 SPECIFICATIONS

## Features and Options

- DMR TII Conventional
- Prodigy™ Plus Mode\*
- Analog Conventional
- Group and Private Calling
- PTT ID
- Text Messaging
- Scanning & Priority Scanning
- Radio Check
- Remote Radio Monitor
- Radio Enable/Disable
- Call Alert
- One Touch Access
- Emergency Alarms
- Man Down Alert
- Lone Worker Alert
- Advanced Digital Encryption\*
- Roaming\*
- GPS\*
- DTMF, 2-Tone, 5-Tone and MDC1200 Signalling Options
- Up to 8 Programmable Function Keys
- X-Sound+HD Enhanced Audio
- Large 1.8 inch Full Color LCD Display
- Ergonomic Design with Large Knobs and Keys
- Battery Pack with High Quality Japanese Cells
- IP67 Design
- 3 Year Warranty

\*Optional Features



GENERAL SPECIFICATIONS	
<b>Model</b>	RDR4220 / RDR4250 / RDR4280
<b>Communication Protocols &amp; Standards</b>	DMR TII ETSI-TS102 361-1, -2, -3 Analog Conventional
<b>Frequency Bands</b>	136-174MHz* / 400-512MHz
<b>Channel Capacity</b>	16 / 1000 (model dependent)
<b>Channel Spacing</b>	12.5KHz / 25KHz
<b>Operating Voltage</b>	8.4V (Max) 7.4V (Nominal)
<b>Battery Pack</b>	2300mAh (Lithium battery)
<b>Current Drain (Approx.)</b>	Standby: 0.14A TX: 1.4A RX: 0.35A
<b>Working Time (5-5-90 duty cycle, high TX power)</b>	Analog: up to 10h Digital: up to 14h
<b>Dimensions (Standard battery, not including antenna)</b>	5.1 x 2.2 x 1.4 inch (H*W*D) 130.2 x 57 x 35.8 mm (H*W*D)
<b>Weight (Standard battery, including antenna)</b>	With LCD Display- 365gr. (12.8oz) No LCD Display- 340gr. (11.9oz)
<b>Antenna Impedance</b>	50Ω
<b>Antenna Gain</b>	0dBi
<b>LCD Display</b>	1.8 inches, 160x128pixel, Full Color
<b>Digital Voice Vocoder</b>	AMBE+2
<b>Emission Designators</b>	Analog 1K0F3E, 16K0F3E Digital 7K60F1D, 7K60F1E

TRANSMITTER	
<b>Power Output</b>	5 Watts VHF / 4 Watts UHF
<b>FM Modulation</b>	11K0F3E@12.5KHz
<b>4FSK Digital Modulation</b>	12.5kHz Data: 7K60F1D 12.5kHz Voice: 7K60F1E
<b>Frequency Stability</b>	±1ppm
<b>FSK Error</b>	≤3%
<b>Conducted / Radiated Emission</b>	-36dBm < 1GHz; -30dBm > 1GHz
<b>Modulation Limiting</b>	±2.5KHz@12.5KHz; ±5.0KHz@25KHz
<b>FM Hum and Noise</b>	40dB@12.5KHz; 45dB@25KHz
<b>Adjacent Channel Power</b>	60dB(12.5kHz); 70dB( 25kHz)
<b>Audio Response</b>	+1 dB to -3 dB
<b>Audio Distortion</b>	≤3%

ENVIRONMENTAL SPECIFICATIONS	
<b>Operation temperature/ Storage temperature</b>	-4°F~+140°F (-20°C~+60°C) / -40°F~+122°F (-40°C~+50°C)
<b>ESD</b>	IEC 61000-4-2 (level 4); ±8KV(contact); ±15KV(air)
<b>Designed to meet Environmental Test Standard for Temperature, Fall, Vibration</b>	MIL-STD-810 C; D; E; F; G
<b>IP Rating</b>	IP67

RECEIVER	
<b>Sensitivity</b>	Analog 0.22µV (12dB SINAD) Digital 0.2µV (5% BER)
<b>Intermodulation (TIA603D)</b>	70dB
<b>Adjacent Channel Selectivity (TIA603A)</b>	60dB@12.5KHz / 70dB@25KHz
<b>Adjacent Channel Selectivity (TIA603D)</b>	60dB@12.5KHz / 70dB@25KHz
<b>Spurious Rejection (TIA603D)</b>	70dB
<b>Hum and Noise</b>	-40dB@12.5KHz; -45dB@25KHz
<b>RX Max. Audio</b>	0.75W at 3% Distortion / Max 1.5W
<b>Rated Audio Distortion</b>	≤3%
<b>Audio Response</b>	+1 dB to -3 dB
<b>Conducted Spurious Emission (TIA603D)</b>	< -57dBm

INTRINSICALLY SAFE CERTIFICATION	
UL 913 5th Ed., TIA 4950-A, CSA C22.2 No. 157- 92 I Class I, II, III; Division 1, Groups C-G; Division 2, Groups A-G; Temp T3C. (*Requires B4223LIIS Battery)	
<b>GPS</b> Accuracy is applicable for long time tracking. (95% with -130dBm signal strength, and min. 5 accessible satellites)	
<b>TTFF Cold Start</b>	< 60 sec
<b>TTFF Hot Start</b>	< 10 sec
<b>Horizontal Location Accuracy</b>	< 16.5 ft. (< 5 m.)

\* Release Q1 2022

Disclaimer: The above specifications are tested according to the listed standards. Due to continuous technical development, they are subject to changes at any time without a prior notice.

For more information, visit [RCACommunicationsSystems.com](http://RCACommunicationsSystems.com)

# ACCESSORIES & OPTIONS

## RDR4220 / RDR4250 / RDR4280 ACCESSORIES



**Heavy Duty IP67  
Speaker Mic**  
SM380WP-X83



**Heavy Duty IP67  
Noise Cancelling  
Speaker Mic**  
SM480WPNC-X83



**2-Wire Surveillance  
Kit**  
SK28NE-X83



**High Noise Reduction  
Noise Cancelling  
BTH Headset**  
HS780NRNC-X83



**VHF / UHF Whip  
Antenna with GPS**  
ANH4200V/U-WG



**VHF /UHF Stubby  
Antennas**  
ANH200V/U-S  
VHF/UHF



**Standard Battery**  
B4223LI  
Lithium-Ion  
7.4V 2300mAh 17.02 Wh



**Intrinsically Safe  
Battery**  
B4223LIIS  
Lithium-Ion  
7.4V 2300mAh 17.02 Wh



**Nylon Holsters - Fixed/  
Swivel Clip/Belt Loop**  
HN4220/80FC/SC/FL/SL



**Heavy Duty Belt Clip**  
BC4200



**Single Unit Desktop  
Rapid Charger**  
CH4201



**6 Bank Multi Unit  
Rapid Charger**  
CH4206



[www.rcacommunicationssystem.com](http://www.rcacommunicationssystem.com)  
[products@rcacommunicationssystem.com](mailto:products@rcacommunicationssystem.com)  
(877) 822-2915  
Created in U.S.A.

### Authorized Dealer:



California Preparedness Resource  
[www.CalPrepResource.org](http://www.CalPrepResource.org)  
(951) 236-8975  
[Bob@CalPrepResource.org](mailto:Bob@CalPrepResource.org)